



AMB Oils GreenCargo SAE 5w30

AMB Oils GreenCargo SAE 5W30 is fully-synthetic, fuel saving, low-ash motor oil for heavy good vehicles based on latest additives technology(Low SAPS- reduced sulfated ash, low phosphorus and sulphur content) with highest quality base oil. Cold viscosity SAE 5W ensure reliable cold starting in extreme temperatures and quickest possible care. **AMB Oils GreenCargo SAE 5W30** is high performance motor oil for commercial vehicles, excellent for use in Euro 4, Euro 5 and Euro 6 engines with or without particulate filters and catalytic converter in conjunction with low-sulphur diesel fuels.

Application

AMB GreenCargo SAE 5w30 is all seasons oil for Euro 4, Euro 5 and Euro 6 standarts.

Performance level:

ACEA E6 / E7 / E9
API CJ-4/CI-4 SN
MB 228.31 / 228.51
MAN M 3677 / MAN M 3477 / MAN M 3271-1
Volvo VDS-4 / VDS-3
Mack EO-O Premium Plus / EO-N
Renault VI RLD-3/RLD-2
MTU Type 3.1
Renault VI RXD / RGD
Mack EO-M Plus
Cummins CES 20081
CAT ECF-3
JASO DH-2
Iveco, Scania, DAF

Technical Characteristics

Excellent viscosity characteristics and shear stability,
Low ash, sulphur and phosphorus "Low SAPS",
Fuel savings under all operating conditions,
Very good detergent and dispersant characteristics,
Extensive protection against wear, corrosion and foaming,
Excellent cold start properties,
Suitable for catalysts,
Extended oil change intervals to protect natural resources.

Technical details

Characteristics	Data	Unit	Test according to
Colour	Brown		Visual
Density at 15°C	855	kg/l	D 4052
Viscosity at 40°C	70,20	mm ² /s	D 445
Viscosity at 100°C	11,80	mm ² /s	D 445
Viscosity index	165		D 2270
Flash Point (COC)	212	°C	D 92
Pour Point	-44	°C	D 6892

All indicated data are approximate values and are subject to the commercial fluctuations.

